



VHF AND UHF TRANSCEIVERS

IC-F110 IC-F210



- **8-Character Alphanumeric Display**

The alphanumeric LCD indicates channel, bank name and decoded text, etc. Various status icons for such functions as an S-meter and output power, etc., enhance the array of information available to the user.

- **128 Memory Channels with 8 Memory Banks**

Up to 128 channels with 8-character channel names can be stored and divided into 8 banks for flexible channel management.

- **6 Prog. Buttons and Independent Volume Knob**

The up/down and P0-P3 buttons allow you to customize the use of the IC-F110/F210 meet your specific needs. The independent volume knob provides quick and easy operation. An advanced radio that is simple to use.

- **Built-in 2-Tone, 5-Tone, CTCSS, DTCS Encoder and Decoder and DTMF Encoder**

Multiple signaling systems are equipped as standard. 8 DTMF auto-dialing memories are available. The optional DTMF decoder UT-108 provides ANI function.

- **4W (typ.) Front-mounted Speaker**

- **Programmable Wide/ Narrow Channel Spacing for Each Channel**

- **Optional Voice Scrambler, UT-109/ UT-110**



icom Inc.

ADDITIONAL FEATURES

Advanced Multi 2-Tone/5-Tone systems

- Programmable actions when a matched tone is received
 - Bell icon indication ON/OFF/Blink
 - Answer back calls
 - Beep sounds
 - Scan Start/Stop
 - Auto transmission
 - Stun/Kill functions (prevents use of a lost or stolen radio)
 - External out for horn drive (Optional OPC-617 is required)
- 32 Tx and 9 Rx 5-Tone codes available
- 11 Tx and Rx 2-Tone codes available

Other features

- Hook scan function and Hook scan ON/OFF button are assignable
- 10 scanning lists and normal/priority scan
- Power on password
- Reduced chassis length (117.5mm) allows for easier installation
- External I/O terminal socket with optional OPC-617
- SmarTrunkII™ or LTR® Trunking capability with optional UT-105 or UT-111, respectively
- Backlit LCD and keys for night time operations
- Meets MIL-STD 810 C, D, E and F specifications

SPECIFICATIONS

GENERAL

- Frequency coverage :

IC-F110	136–174MHz
IC-F210	400–430MHz
	440–490MHz
- Number of channels : Max. 128, 8 banks
- Channel Spacing : 12.5/25kHz, 12.5/20kHz
- PLL channel step : 2.5, 3.125kHz (VHF)
5, 6.25kHz (UHF)
- Frequency stability : ±1.5kHz
- Operating temp. range : –25°C to +55°C
- Power supply voltage : 13.2V DC
- Current drain : Tx at 25W 7A
Rx Max. audio 1200mA
Stand-by 300mA
- Antenna impedance : 50Ω (SO-239)
- Dimensions : 150(W)×40(H)×117.5(D) mm
- Weight : 800g

TRANSMITTER

- Output power : 25W (at 13.2V DC)
- Max. frequency deviation : ±5.0kHz (wide)
±4.0kHz (middle)
±2.5kHz (narrow)
- Spurious emissions : 0.25μW (below 1GHz)
- Adjacent channel power : 70dB (wide, middle)
60dB (narrow)
- Mic. impedance : 600Ω (8-pin modular)

RECEIVER

- Sensitivity : –4dBμV typ. (emf)
(at 20dB SINAD)
- Squelch sensitivity : –4dBμV typ. (emf, threshold)
- Adjacent channel selectivity : 75dB typ. (wide, middle)
65dB typ. (narrow)
- Spurious response : 75dB
- Intermodulation : 67dB typ.
- Audio output power : 4.0W typ. at 10% dist./4Ω load
- Ext. SP connector : 2-conductor 3.5(d)mm/4Ω

Applicable U.S. Military Specifications

The IC-F110/F210 meets MIL-STD requirements and strict environmental standard for shock (MIL 810 C, D, E and F) and vibration (MIL 810 C, D, E and F).

Supplied Accessories

- Hand mic. (HM-100N)
- DC power cable
- Mounting bracket kit
- Hanger kit
- Key assign stickers

Measurements made in accordance with ETS 300 086. All stated specifications are subject to change without notice or obligation.

OPTIONS

- **HM-100TN** DTMF MICROPHONE
- **OPC-617** ACC CABLE
For external terminal connection.
- **SM-25** DESKTOP MICROPHONE
Convenient for dispatching, equipped with monitor switch.

- **SP-5 / SP-10 / SP-22** EXTERNAL SPEAKERS
Compact and easy-to-install.
Input impedance: 4Ω; Max. input power: 5W
- **UT-105** SmarTrunk II™ Logic Board
SmarTrunk II is a trademark of SmarTrunk Systems, Inc.
- **UT-108** DTMF DECODER UNIT
Provides DTMF decode and ANI capabilities.

- **UT-109** VOICE SCRAMBLER UNIT (Version 02)
- **UT-110** VOICE SCRAMBLER UNIT (Version 02)
The scrambler systems of the UT-109 and UT-110 are not compatible with each other. Ask your dealer for details.
- **UT-111** LTR® Trunking UNIT
LTR is a registered trademark of E.F. Johnson Company.



Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: 06 6793 5302 Fax: 06 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Your local distributor/dealer:

AUTHORIZED DEALER

LINKWELL TELECOM SERVICES.

1/4, Puranik Building, Near Old Post Office,
Panvel, Navi Mumbai, Maharashtra, India-410 206.

Tel. No. : 022-27462199.

www.linkwelltelecom.com