



144MHz FM TRANSCEIVER

# IC-2300H

## ***Tough & Built to Last*** ***Long Lasting Power and Icom Quality***

- ***65 Watts of RF Output Power with Heavy Duty Endurance***
- ***Powerful 4.5W Audio Output Provides Loud and Clear Audio***
- ***Tested to the Latest MIL-STD 810 G Specifications***



**65 Watts**



**Stable 65W of output power**

The IC-2300H can generate 65W of output power. The rugged aluminum diecast provides effective heat dissipation and keeps RF output even during high duty cycle continuous transmission.

**A total of 207 memory channels**

The IC-2300H has a total of 207 memory channels, including 200 regular channels, 6 scan edges and 1 call channel. The channel name is programmable with 6 characters for easy recognition.

**Built-in CTCSS and DTCS encoder/decoder**

The CTCSS and DTCS tones are built-in for quiet stand-by and repeater access. The tone scan function detects the subaudible tone that is used for repeater access. The pocket beep function gives you an audible and visual indicator of an incoming call. The DTCS encoder function (DTCS transmit only) is also available.

**Simple operation**

The IC-2300H retains the basic panel layout and its user interface from the IC-2200H. A 70.6x20 mm LCD display offers a good viewing angle suitable for mobile operation. The bottom of the display indicates the available functions of the front panel buttons directly below the display.

**SPECIFICATIONS**

GENERAL	
Frequency coverage	TX: 144-148MHz, RX: 136-174MHz* TXRX: 144-148MHz
* Guaranteed range	
Number of channels	207 channels (including 6 scan edges, and 1 call)
Type of emission	F2D, F3E (FM)
Frequency stability	±3ppm
Power supply requirement	13.8V DC ±15%
Current drain (approx.)	
Tx 65W	11A
Rx Max. audio/Stand-by	1.5A/0.4A
Antenna impedance	50Ω (SO-239)
Operating temperature range	-10°C to +60°C; 14°F to +140°F
Dimensions (WxHxD; Projections not included)	140x40x162 mm; 5.51x1.57x6.38 in
Weight (approx.)	1.1 kg; 2.43lb

TRANSMITTER	
Output power (at 13.8V DC)	65W, 25W, 10W, 5W
Max. frequency deviation	±5.0kHz/±2.5kHz (W/N)
Spurious emissions	Less than -60dBc
Microphone impedance	600Ω (8-pin modular)
RECEIVER	
Intermediate frequencies	46.35MHz/450kHz
Sensitivity (at 12dB SINAD)	Less than 0.18μV
Selectivity	Wide More than 6kHz (at 6dB) Less than 14kHz (at 60dB) Narrow More than 3kHz (at 6dB) Less than 9kHz (at 55dB)
Spurious response rejection	More than 60dB
Audio output power	4.5W typ. (10% dist. 4Ω load)
External speaker connector	2-conductor 3.5 (d) mm (1/8")/4Ω

All stated specifications are subject to change without notice or obligation.

**Applicable U.S. Military Specifications**

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D -E and -F.

Supplied Accessories (* Depending on version)	
• Remote control Mic, HM-133V	• Mounting bracket kit
• Microphone hanger*	• DC power cable
	• Spare fuses

**OPTIONS**

Some options may not be available in some countries. Please ask your dealer for details.



- CS-2300H CLONING SOFTWARE + OPC-478/OPC-478UC CLONING CABLES  
OPC-478: RS-232C cable;  
OPC-478UC: USB cable
- OPC-474 CLONING CABLE  
For transceiver to transceiver cloning.
- OPC-1132A, OPC-347 DC POWER CABLES  
OPC-1132A: 3.0m; OPC-347: 7.0m

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia, Japan and/or other countries.

Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0613

[www.icom.co.jp/world](http://www.icom.co.jp/world)

Count on us!

Your local distributor/dealer:

AUTHORIZED DEALER

LINKWELL TELECOM SERVICES.

1/4, Puranik Building, Near Old Post Office,  
Panvel, Navi Mumbai, Maharashtra, India-410 206.

Tel. No. : 022-27462199.

[www.linkwelltelecom.com](http://www.linkwelltelecom.com)