

KENWOOD

NX-5700(B)/5800(B)

VHF/UHF DIGITAL TRANSCEIVER
MULTI-PROTOCOL DIGITAL & ANALOG Mobile RADIOS



NXDN®

NEXEDGE®  Bluetooth®  microSD  GPS  FleetSync®

● FEATURE HIGHLIGHTS

- **Multi-Protocol** operation in P25 (Phase I&II), NXDN® protocols
- **Mixed Digital & FM Analog Operation** allows intelligent migration in mixed sites and easy migration with digital radios in other sites
- **Large, Color 2.55" (154 x 422 pixels) TFT Display** for at-a-glance operational status checking
- **Easy to follow GUI** and Multi-line Text to convey more information
- **Dual Remote Control Head Option** and **Multi-Band (Multi RF Deck) Control Option** providing scalable configurations for various operations and applications
- **Built-In GPS Receiver/Antenna** for effective fleet management
- **Bluetooth® Module built-in** for hands-free operation
- **Active Noise Reduction (ANR)** utilizing built-in DSP for suppression of ambient noise
- **Renowned KENWOOD Digital Audio Quality**
- **Built-in 56-bit DES Encryption**
- **Optional 256-bit AES Encryption**
- **microSD/microSDHC Memory Card Slot** for increased memory capacity for "Voice & Data"
- **IP54/55 and MIL-STD-810 C/D/E/F/G**

● GENERAL FEATURES

- 5 W – 50 W (136-174 MHz) Models
- 5 W – 45 W (380-470, 450-520 MHz) Models
- Maximum of 4,000 CH/Radio capacity, 512 CH/Zone, 128 Zones
- DB-25 Accessory Connector
- 4 W Speaker Audio

● DIGITAL – P25 MODE

- P25 Conventional Trunking (Phase 1/Phase 2) Protocol
- AMBE+2™ Enhanced Vocoder
- Talk Group ID Lists
- Individual ID Lists
- Caller ID Display
- Remote Monitor/Remote Check
- Radio Inhibit
- Encryption Key Zeroize & Retention
- P25 GPS Location
- P25 Over-the-Air Re-keying
- Over-the-Air Programming²

● DIGITAL – NXDN® MODE

- NXDN® Conventional/Trunking Protocol¹
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming²
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging³
- Remote Stun/Kill³
- Remote Check³
- Short & Long Data Messages³
- GPS Location
- NXDN® Digital Scrambler Included

¹ Only supports TYPE-C Protocol

² Requires KENWOOD OTAP Management software.

³ Requires NX subscriber unit PC serial interface compatible software application (e.g. KENWOOD AVL & Dispatch Messaging software) or hardware (e.g. console).

● FM MODES – GENERAL

- Conventional & LTR Zones
- FleetSync®/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT & Two-Tone
- Built-in Voice Inversion Scrambler

● MULTIPLE CONFIGURATIONS (Option)

The NX-5700(B)/5800(B) allows users to create a variety of configurations to suit different requirements by combining different options.

- **Single RF Deck/Single Remote Control Head:**
The simplest configuration can be achieved by turning the front control panel of the NX-5700/5800 into a Remote Control Head.
- **Single RF Deck/Dual Remote Control Heads*:**
One controller can be mounted on the dashboard, with the other at the rear.
- **Dual RF Decks/Single Remote Control Head*:**
You can operate two radios (e.g. VHF and UHF bands) as if they were one by adding an NX-5700B/5800B RF Deck.
- **Dual RF Decks/Dual Remote Control Heads*:**
This adds the convenience of a dual control head to the above configuration. Advantage: 2 operators can control 2 radios (e.g. VHF and UHF bands) from separate control heads.

*Available later



Options

NX-5700B/5800B RF Deck

KCH-19 Basic Control Head Kit

KCH-20R* Featured Control Head

KRK-14H Control Head Interface Kit (adapter for the Head)

KRK-15B Control Head Remote Kit (adapter for the RF Deck)

KCT-71 Remote Control Cable (available in 3 lengths of 17ft (5.2m), 25ft (7.6m), 1.6ft (0.5m)*)

KWD-AE30/AE31 Secure Cryptographic Module

KPG-180AP OTAP Manager

KMC-35 Microphone

KMC-36 Keypad Microphone

KES-3 External Speaker (compact low profile; 3.5 mm plug)

KES-5 External Speaker (40 W max input, requires KAP-2)

KCT-23 DC Power Cable

KCT-46 Ignition Sense Cable

KLF-2 Line Filter

KMB-10 Key Lock Adapter

KAP-2 Horn/Alert/PA Relay Unit

KRA-40G GPS Active Antenna

KPS-15 DC Power Supply (23A max)

Main Specifications

All accessories and options may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

GENERAL	NX-5700(B)	NX-5800(B)
Frequency Range		
Type 1	136-174 MHz	450-520 MHz
Type 2		380-470 MHz
Max. Channels Per Radio	1024 (Up to 4000 CH with option)	
Number of Zones	128	
Max. Channels per Zone	512	
Channel Spacing		
Analog	12.5/15/25*/30* kHz	12.5/25* kHz
Digital	6.25/12.5 kHz	6.25/12.5 kHz
Power Supply	13.6V DC ±15%	
Current Drain		
Standby	0.45 A	
RX	2.3 A	
TX	13 A	
Operating Temperature	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability	±1.0 ppm	
Dimensions (W x H x D)	Projections not included 6.69 x 1.89 x 6.93 in. (170.0 x 48.0 x 176 mm.)	
Weight (net)	3.53 lbs (1.6 kg)	
FCC ID		
Type 1	Pending	K44471200
Type 2		K44471201
IC Certification		
Type 1	Pending	-
Type 2		282F-471201

*25 and 30 kHz are not included in the models sold in the USA or US territories.
Analog measurements made per TIA 603 and specifications shown are typical.
Digital measurements made per TIA 102CAAA and specifications shown are typical.
Specifications are subject to change without notice, due to advancements in technology.

RECEIVER	NX-5700(B)	NX-5800(B)
Sensitivity		
NXDN® 6.25 kHz Digital (3% BER)		0.20 µV
NXDN® 12.5 kHz Digital (3% BER)		0.25 µV
P25 Digital (5% BER)		0.25 µV
P25 Digital (1% BER)		0.40 µV
Analog (12dB SINAD)		0.25 µV
Selectivity		
P25 Digital		63 dB
Analog @12.5 kHz		71 dB
Analog @ 25 kHz		81 dB
Intermodulation		80 dB
Spurious Rejection		85 dB
Audio Distortion		
Digital		2%
Audio Output Power	4W/4 Ω (Remote Control Head: 3 W/4 Ω)	
TRANSMITTER		
RF Power Output	50 W to 5 W	45 W to 5 W
Spurious Emission	-73 dB	-75 dB
FM Hum & Noise		
Analog @ 12.5 kHz		45 dB
Analog @ 25 kHz		50 dB
Audio Distortion		2%
Modulation	16K0F3E, 11K0F3E, 8K10F1E, 8K10F1D, 8K10F1W, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.
SD and microSD are trademarks of SD-3C, LLC in the United States, and/or other countries.
AMBE+2™ is a trademark of Digital Voice Systems Inc.
NXDN® is a trademark of JVC KENWOOD Corporation and Icom Inc.
NEXEDGE® is a registered trademark of JVC KENWOOD Corporation.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain*	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure I, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water	IP54/55**				

*1: Blowing rain protection for the Remote Control Head only. *2: IP54: RF Deck; IP55: Remote Control Head

KENWOOD

AUTHORIZED DEALER

LINKWELL TELECOM SERVICES.

1/4, Puranik Building, Near Old Post Office,
Panvel, Navi Mumbai, Maharashtra, India-410 206.

Tel. No. : 022-27462199.

www.linkwelltelecom.com



ISO9001 Registered

Professional Systems Business Group
JVC KENWOOD Corporation

ADS#35014 Printed in USA