

# Door Access Control

## C3-200



### Specification

Number of Doors Controlled : 2 Door  
Card Holders Capacity : 30,000  
Log Events Capacity : 100,000  
Communication : TCP/IP and RS-485  
Number of Readers Supported : 8(4 RS-485 Reader,  
4 26-bit wiegand reader)  
Types of Readers Supported : 26-bit Wiegand,  
others upon request  
Number of Inputs : 6 (2Exit Device, 2 Door Status,  
2AUX)  
Number of Outputs : 4 (2-From C Relay for  
Lock and 2-Form C Relay for Aux Output)  
Weight : 7.5lbs (3.4kg)  
Enclosure : Powder Coated Aluminium  
Mounting : Wall Mount  
Recommended Power Supply : 12V DC, 1.5A  
Dimensions (Bundle Only) : 380mm(L)X80mm(W)  
X 280mm(H)  
Dimensions ( Board Only) : (160mm×106mm)

AUTHORIZED DEALER

LINKWELL TELECOM SERVICES,  
1/4, Puranik Building, Near Old Post Office,  
Panvel, Navi Mumbai, Maharashtra, India-410 206.  
Tel. No. : 022-27462199.  
www.linkwelltelecom.com

#### Features:

- ▶ 256 time Zones, 256 access levels
- ▶ Anti-passback function
- ▶ Interlock function , Linkage function
- ▶ Multi-Card Opening function, Remote door opening and closing
- ▶ Real-Time monitoring Via Web browser
- ▶ 2 auxiliary input may be connected to infrared body detectors,
- ▶ Fire alarms, smoke detectors etc.
- ▶ 2 auxiliary output may be connected to alarms, cameras,door bells etc.
- ▶ TCP/IP and RS485 communication
- ▶ Built-in Auxiliary input and Output
- ▶ Access Control Functions
- ▶ Support full range of card readers

#### Software and Database Supported :

Access Security System 3.5 (Desktop Version)

Database Type:- MS Access / MS SQL

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development